ELETTROVENTILATORI PER ORGANO

GAMMA DI PRESSIONI: 120 - 140 mm/H_2O

1400 giri al minuto / 50 Hz. – **1680** giri al minuto / 60 Hz.

Altri tipi di frequenza, voltaggio e pressione a richiesta.

Disponibili nella forma standard, oppure nelle forme come in figura, con costo aggiuntivo.

Riservato il diritto di apportare qualsiasi necessaria variazione.

ORGAN BLOWERS

PRESSURE RANGE: 120 - 140 mm/H_2O

1400 r.p.m. / 50 Hz. - **1680** r.p.m. / 60 Hz.

Other types of current, voltages and wind pressures on request.

Available in shape standard or in shapes as in figure at additional charge.

We riserve the right to make any necessari alterations.

TRIFASE A.C. 110/230/400 V.	MONOFASE A.C. 110/230 V.	Per registri D'organo	Portata **m^3/min**	Portata **CFM**	Pressione **mm/H_20**	Pressione PA ca.	Potenza motore HP	Potenza motore KW	Peso netto KG ca.	Peso lordo KG ca
3 p.h. A.C. 110/230/400 V.	1 ph. A.C. 110/230/ V.	For organ stops app.	Wind Product.	Wind Product.	Wind pressure	Wind pressure	Motor power	Motor power	Net weight approx.	Gross weight approx.
13000	13000A	30 - 35	22	777	120	1200	1	0.74	110	130
13001	13001A	30 - 35	22	777	140	1400	1.1	0.81	112	132
13002	13002A	40 - 45	28	989	120	1200	1.5	1.11	115	135
13003	13003A	40 - 45	28	989	140	1400	1.6	1.18	116	
13004	13004A	50 - 55	36	1272	120	1200	2	1.48	120	140
13005	13005A	50 - 55	36	1272	140	1400	2.1	1.55	121	141
13006	13006A	60 - 65	43	1519	120	1200	2.5	1.85	130	150
13007	13007A	60 - 65	43	1519	140	1400	2.6	1.92	131	151
13008	13008A	60 - 68	43	1519	160	1600	2,8	2.07	140	165
13009	13009A	60 - 70	43	1519	180	1800	3.0	2,22	145	170

DIMENSIONI ELETTROVENTILATORI 1400 GIRI

Dimensioni approssimative in millimetri.

DIMENSIONS ORGAN BLOWERS 1400 R.P.M.

Approximate dimensions in millimetres .

Trifase A.C. 3 ph.	Monofase 1 ph A.C.	A	B	C	D	E	F	G	H	I	K	L	M	N	O	P	R	S	T	U
13000	13000A	800	873	902	750	320	194	323	685	80	185	255	825	630	80	920	770	895	255	310
13001	13001A	800	873	902	750	320	194	323	685	80	185	255	825	630	80	920	770	895	255	310
13002	13002A	800	873	902	750	320	194	323	685	80	185	255	825	630	80	920	770	895	255	310
13003	13003A	800	873	902	750	320	194	323	685	80	185	255	825	630	80	920	770	895	255	310
13004	13004A	800	873	902	750	320	194	323	685	80	185	255	825	630	80	920	770	895	255	310
13005	13005A	800	873	902	750	320	194	323	685	80	185	255	825	630	80	920	770	895	255	310
13006	13006A	800	873	902	750	320	194	323	685	80	185	255	825	630	80	920	770	895	255	310
13007	13007A	800	873	902	750	320	194	323	685	80	185	255	825	630	80	920	770	895	255	310
13008	13008A	950	1030	910	758	395	195	320	693	80	185	255	975	705	80	1070	850	1045	255	310
13009	13009A	950	1030	910	758	395	195	320	693	80	185	255	975	705	80	1070	850	1045	255	310